

Feast Watson Prooftint**AUDW0729**

Part A	331-line
--------	----------

Description

Feast Watson PROOFTINT is a unique concentrated spirit based dye stain that allows the full clarity of the timber grain to show through after staining. PROOFTINT is suitable for all interior timber, including furniture, doors, architraves and floors, and is suitable for use on all timber varieties including pine. PROOFTINT is a versatile stain that can be applied directly to the surface or diluted in Feast Watson PROOFTINT COLOUR REDUCER or Feast Watson TIMBER PRIMER. Additionally, PROOFTINT can be added to Feast Watson CLEAR VARNISH to create a one-step stain and varnish, or added to Feast Watson LIMING SOLUTION to achieve a range of soft pastel shades. PROOFTINT colours can be mixed together to create your own custom shade or to achieve colour matches for your timber.

Features

- Spirit- based stain
- Brush on-wipe off application
- Semi-transparent
- Add to turps-thinned products

Benefits

- Quick drying
- Colour depth control
- Enhances natural grain and colour
- Can be used in most clear varnishes

Uses

Use FEAST WATSON Prooftint Stain on all interior timbers, panelling, cupboards, furniture, wet areas, where it is desirable to stain then seal with a hard clear coating

Precautions And Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.
Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather	For interior use only.
---------	------------------------

Typical Properties			
Colour	13 packaged colours	Components	1
Number Of Coats	1 or 2	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.
V.O.C. Level	< 915g/L		
Clean Up Description	Clean brushes and other equipment using methylated spirits. When mixing PROOFTINT with another coating, follow the cleaning instructions of the base coating. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.		
Application Method	 Brush Other: Rag		
Application Conditions	Min Wet Film Per Coat (microns) Dry Film Per Coat (microns) Recoat Time (min) Theoretical Spread Rate (m²/L) 10	Max	Recommended
Typical Properties Notes	COVERAGE Approximately 10 - 20m ² per litre, depending on porosity of timber. DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Re-coat: 30 minutes when used neat; 1 hour when diluted. Top coat: 30 minutes when used neat; 12 hours when diluted.		

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> * New Timber Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson SANDING SEALER and sand back as per the directions. Seal soft porous timbers, such as Pine, Meranti and Cedar with TIMBER PRIMER to ensure even absorption into the timber. Previously Coated Timber Previously coated surfaces need to be sanded back to bare timber. Remove all sanding dust before staining.
Application Procedure And Equipment	<ul style="list-style-type: none"> * Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Colour can be varied by mixing PROOFTINT colours and adding PROOFTINT COLOUR REDUCER. Note: The dwell time before wiping excess, and the finishing clear coat will impact the final colour. For Small Areas For small and detailed areas, apply PROOFTINT mix directly to the surface in the direction of the grain, by either brush or rag. Wipe off after 2-5 minutes depending on the depth of colour required. Allow to dry, then seal with CLEAR VARNISH as per the label instructions. For Large Areas For large areas including floors, dilute PROOFTINT in PROOFTINT COLOUR REDUCER which will give more working time to distribute the stain evenly. Apply with a rag, brush or Feast Watson FLOOR FINISH APPLICATOR in the direction of the grain. Wipe off excess after a period of time determined by the desired colour intensity. Allow to dry, then seal with FLOORSEAL OIL, FLOORCLEAR or FLOORPROOF PRO as per the label instructions. Stain & Varnish Method Add up to 10% PROOFTINT to CLEAR VARNISH or LIMING SOLUTION and apply as per the label instructions.

Health And Safety			
MSDS Number	14605701	Using Safety Precautions	Avoid contact with skin and eyes and breathing in vapour or spray mist. Wear overalls, impervious gloves and chemical goggles. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/particulate respirator. Keep containers closed when not in use. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Do not empty into drains.
Health Effects	<p>FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p> <p>INHALED: Remove from contaminated area.</p>	Flammability	This product is flammable
Protective Equipment	Personal Protective Equipment: Wear eye protection, protective clothing and gloves.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerb side recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	331-line	Shipment Name	PAINTS
Size 1 Litre 250ml 125ml 50ml		Weight 1.0kg 0.30kg 0.15kg 0.06kg	
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427