

Feast Watson Scandinavian Oil

AUDW0743

Part A	870 94643
---------------	-----------

Description

Feast Watson SCANDINAVIAN OIL is a clear blend of penetrating oils and polyurethane resin that gives an attractive protective finish on fine interior woodwork projects. SCANDINAVIAN OIL may be applied directly to raw or previously coated timber to provide a matt finish which can be built to a satin lustre by applying additional coats.

Features

- Superior finish.
- Rejuvenates the timber.
- Fine, silky smooth matt to satin lustre finish.

Benefits

- Highlights or restores the natural grain and colour of timber.
- Removes any accumulated scratches.
- Beautiful finish.

Uses



Ideal for all interior woodwork including furniture, architraves, trims, cedar blinds and panelling.

Precautions And Limitations

Do NOT apply in temperatures under 10°C or is likely to fall below 10°C during the drying period..
For interior use only.

Performance Guide

Weather	For interior use only.	Salt	Unaffected by splash.
Heat Resistance	Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.	Water	Good water resistance.
Solvent	Resists mineral turpentine and similar solvents.	Abrasion	Moderate resistance to abrasion.

Typical Properties																											
Gloss Level	Matt	Colour	Clear																								
Components	1	Number Of Coats	2+																								
Toxicity	Lead free.	V.O.C. Level	< 560g/L																								
Touch Dry	4 hours																										
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	  Brush Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">32</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">56</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">18</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">8 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td style="text-align: center;">18</td> <td style="text-align: center;">18</td> </tr> </table>			Solids By Volume	32				Min	Max	Recommended	Wet Film Per Coat (microns)			56	Dry Film Per Coat (microns)			18	Recoat Time (min)	8 hours			Theoretical Spread Rate (m²/L)		18	18
Solids By Volume	32																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			56																								
Dry Film Per Coat (microns)			18																								
Recoat Time (min)	8 hours																										
Theoretical Spread Rate (m²/L)		18	18																								
Typical Properties Notes	COVERAGE 15 to 18m ² per litre. DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> ▪ New Timber Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson SANDING SEALER and sand back as per the directions. Previously Coated Timber Clean previously varnished surfaces with Feast Watson FLOORCLEAN and allow to dry.
Application Procedure And Equipment	<ul style="list-style-type: none"> ▪ Surfaces to be coated must be dry and free from all dirt, dust, grease, wax and oil. SCANDINAVIAN OIL should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. New Timber Apply a coat of SCANDINAVIAN OIL using a clean soft cloth or pad, which is thoroughly saturated, or apply with a brush and then work the SCANDINAVIAN OIL into the timber with a clean soft cloth or pad. Coated Timber Apply using a scouring pad or fine steel wool (000). Allow to penetrate for 30 minutes. When the surface gets tacky remove excess surface oil with a clean dry cloth. Allow 8 hours between coats. Apply further coats until the desired finish is achieved. Three or four coats are recommended for a satin lustre and durable protection. More coats will increase the sheen.

Health And Safety			
MSDS Number	2609	Using Safety Precautions	Irritating to skin. Avoid contact with skin and eyes. Use only in well ventilated areas. Keep windows and doors open during use and while drying. If inhalation risk exists wear organic vapour/particulate respirator. Keep away from sources of ignition. Do NOT smoke. Keep containers closed when not in use.
Health Effects	FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: Rinse with plenty of running water. Seek medical help if irritation occurs. SKIN: Wash contaminated skin with plenty of soap and water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. INHALED: Remove from contaminated area. Apply artificial respiration if not breathing.	Flammability	This product is flammable.
Protective Equipment	Wear overalls, impervious gloves and safety glasses.	Storage	Keep out of reach of children.
Disposal	Do NOT pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council/Waste Management Authority first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	870 94643	Shipment Name	PAINTS
Size	4L 1 L 500ml 250ml	Weight	3.5Kg 0.9Kg 0.5Kg 0.3Kg
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427