

Feast Watson Traditional Timber Oil

AU_DW01795

Part A	840 94621
---------------	-----------

Description

Feast Watson TRADITIONAL TIMBER OIL is a deep penetrating oil for a classic finish on decking and exterior timber. TRADITIONAL TIMBER OIL protects timber against the destructive effects of weather and mould growth. The added eucalyptus oil naturally dissolves gum residue and grease, ensuring an even finish. TRADITIONAL TIMBER OIL is a warm natural colour which can be tinted to highlight the character of timber species. TRADITIONAL TIMBER OIL weathers naturally and will not crack or peel and is ideal for use on all exterior timber including decking, steps, fences, gates, posts and beams.

Features

- Traditional oil
- Deep penetrating

Benefits

- Classic finish
- Natural timber look

Uses





Use on all exterior timber including decking, steps, fences, gates, posts and beams.

Precautions And Limitations

Do not apply this product in temperatures below 10°C or above 35°C, or when rain or heavy dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight and coat in the shade.

Performance Guide

Weather	For exterior use.	Salt	Unaffected by splash or spillage.
Heat Resistance	Up to 120C.	Water	Good water repellency.
Solvent	Resists mineral turpentine and similar solvents.	Abrasion	Good resistance to foot traffic.
Acid	N/A	Alkali	N/A

Typical Properties																											
Gloss Level	Matt	Colour	Natural																								
Components	1	Number Of Coats	2																								
Toxicity	Lead free	V.O.C. Level	< 605g/L																								
Touch Dry	2 hours																										
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	    Air Spray Brush Roller Pad																										
Application Conditions	<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Solids By Volume</td> <td style="text-align: center;">24</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td style="text-align: right;">Wet Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;">Dry Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;">Recoat Time (min)</td> <td style="text-align: center;">1 hour</td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;">Theoretical Spread Rate (m²/L)</td> <td></td> <td style="text-align: center;">10</td> <td style="text-align: center;">10</td> </tr> </table>			Solids By Volume	24				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	1 hour			Theoretical Spread Rate (m²/L)		10	10
Solids By Volume	24																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	1 hour																										
Theoretical Spread Rate (m²/L)		10	10																								
Typical Properties Notes	<p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Recoat: 1 hour Dry: 18 hours</p> <p>COVERAGE Softwood: 6 - 8m² per litre Hardwood: 8 - 10m² per litre</p>																										

Application Guide

Surface Preparation	<ul style="list-style-type: none"> NEW TIMBER Allow new timber to weather in its final position for 4 - 6 weeks. Prepare timber for coating with Feast Watson WOODCLEAN as per the instructions. For best results, lightly sand the surface to remove any grain raise. Remove all sanding dust before coating. WEATHERED TIMBER Prepare weathered or grey timber by cleaning thoroughly with WOODCLEAN as per the instructions. Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating. PREVIOUSLY COATED TIMBER Timber coated with stain or oil can be coated with TRADITIONAL TIMBER OIL after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber: if the water absorbs into the timber it is suitable for coating. If the water beads, further weathering, sanding or stripping is required. Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding. Prepare timber for coating with WOODCLEAN as per the instructions.
Application Procedure And Equipment	<ul style="list-style-type: none"> Allow the timber to dry completely before applying TRADITIONAL TIMBER OIL. TRADITIONAL TIMBER OIL should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. If the job requires more than one can of oil, mix all together in one large container prior to commencing. Apply one flood coat of TRADITIONAL TIMBER OIL using a brush, roller, spray or Feast Watson Floor Applicator. If applying with a roller or spray, back brush the coating to ensure even penetration. Work along 3 - 4 planks at a time, in the direction of the grain. Ensure edges and end grain are fully coated. Allow to penetrate into the timber for 30 - 60 minutes, then wipe off excess product with dry applicator or cloth before surface becomes tacky. Allow to dry for a further 60 minutes. Apply a second coat as above, allow to penetrate for 30 - 60 minutes and again wipe off excess with dry applicator or cloth before surface becomes tacky. WIPING EXCESS IS NECESSARY TO ENSURE AN EVEN FINISH. For a longer lasting finish, a third coat may be applied after 1 hour to the same method as above. Allow to dry for 18 hours before light foot traffic. MAINTENANCE Regularly monitor coated timber for signs of colour loss, dryness and weathering. Recoat the timber when it begins to show signs of dryness to help maintain its natural beauty and protection. When required, clean the surface using WOODCLEAN, allow the surface to dry and recoat with one coat of TRADITIONAL TIMBER OIL. Wipe excess after 30 - 60 minutes to ensure an even finish. For a longer lasting finish, a second coat may be applied after 1 hour.

Health And Safety

MSDS Number	1236	Using Safety Precautions	RISK: Flammable. Irritating to skin. May cause sensitisation by skin contact. Harmful: May cause lung damage if swallowed. Avoid contact with skin and eyes. Provide adequate ventilation. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
Health Effects	<p>FIRST AID: For advice contact a Doctor or Poisons Information Centre on AUST 13 11 26, NZ 0800 764 766.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.</p>	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council first.		

In the case of emergency, please call 1800 033 111

Transport And Storage			
Pack A	840 94621	Shipment Name	PAINT
Size 4L 10L	Weight 3.8kg 9.4kg		
Flash Point	>23°C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427