

## Feast Watson Liming White Floor Finish Satin

**AU\_DW01800**

<b>Part A</b>	710 W0053
---------------	-----------

### Description

Feast Watson LIMING WHITE FLOOR FINISH combines a water based lime stain with a professional clear polyurethane for one-step 'soft milky white colour' and durable protection on interior timber flooring. LIMING WHITE FLOOR FINISH is a non-yellowing, semi-transparent coating that allows the grain pattern of timber to remain visible. One coat gives a subtle, pale colour; multiple coats will build the opacity and whiteness.

### Features

- Lime stain combined with a durable clear
- Retains timber grain
- Extra coats build colour and depth
- Water based
- Fast drying- 2hr recoat

### Benefits

- No clear top coat required
- Will not yellow over time
- Complete flooring project in a day
- Low odour

### Uses





All interior timber flooring

### Precautions And Limitations

This is a three coat flooring system. If the desired colour is achieved in less than three coats, complete the system with a suitable water based floor coating, such as Cabot's CFP or Intergrain ULTRAFLOOR, as per label instructions  
Do NOT apply this product at temperatures below 10°C or above 35°C.

### Performance Guide

<b>Weather</b>	Interior Only	<b>Salt</b>	N/A
<b>Heat Resistance</b>	Softens at temperatures above 70C	<b>Water</b>	Good water resistance, unaffected by splash or spillage
<b>Solvent</b>	Sensitive to aromatic hydrocarbons, alcohols and ketones	<b>Abrasion</b>	Good Resistance to Abrasion
<b>Acid</b>	N/A	<b>Alkali</b>	N/A

Typical Properties																											
<b>Gloss Level</b>	Satin	<b>Thinner</b>	Water																								
<b>Colour</b>	Liming White	<b>Components</b>	1																								
<b>Number Of Coats</b>	1+	<b>Toxicity</b>	Lead Free																								
<b>V.O.C. Level</b>	<70 g/l	<b>Meets GBCA VOC Requirement?</b>	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																								
<b>Touch Dry</b>	30 min																										
<b>Clean Up</b>	 Water																										
<b>Application Method</b>	   Brush    Roller    Pad																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">26</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>Recoat Time (min)</b></td> <td style="text-align: center;">2 hours</td> <td></td> <td></td> </tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td> <td></td> <td style="text-align: center;">12</td> <td></td> </tr> </table>			<b>Solids By Volume</b>	26				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>				<b>Dry Film Per Coat (microns)</b>				<b>Recoat Time (min)</b>	2 hours			<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>		12	
<b>Solids By Volume</b>	26																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>																											
<b>Dry Film Per Coat (microns)</b>																											
<b>Recoat Time (min)</b>	2 hours																										
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>		12																									
<b>Typical Properties Notes</b>	<p><b>DRYING TIME</b> Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 30 minutes. Recoat: 2 hours. Allow 24 hours before light foot traffic and 72 hours for normal traffic. Full curing after 7 days.</p> <p><b>COVERAGE</b> Softwood: 8 - 10m<sup>2</sup> per litre. Hardwood: 10 - 12m<sup>2</sup> per litre. Cork: 8 - 10m<sup>2</sup> per litre.</p>																										

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>NEW OR BARE TIMBER/CORK Punch exposed nails below the surface. Holes and imperfections should be filled with timber putty. Sand timber to an even, smooth surface. Vacuum and wipe to remove dust. Prepare uncoated cork tiles in accordance with the supplier's recommendation.</li> <li>PREVIOUSLY COATED TIMBER Previously coated surfaces need to be sanded back to bare timber. Remove all sanding dust before coating.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Stir LIMING WHITE FLOOR FINISH thoroughly before and during use with a flat blade stirrer, being careful not to introduce bubbles. If using more than one can of the same colour to complete a job, combine both cans and stir thoroughly.</li> <li>Test colour on an off-cut or inconspicuous area prior to coating the whole job to ensure satisfaction with colour choice.</li> <li>Apply with a Feast Watson FLOOR FINISH APPLICATOR, brush or short nap mohair roller. Work along the whole length of 3 - 4 floorboards at a time, maintaining a wet edge to prevent lap marks and lay off in the direction of the grain. Take care to not introduce bubbles. This is a three coat flooring system. If the desired colour is achieved in less than three coats, complete the system with a suitable water based floor coating, such as Cabot's CFP or Intergrain ULTRAFLOOR, as per label instructions.</li> <li>Stronger colour can be developed with further coats of LIMING WHITE FLOOR FINISH. Continue applying coats by the above procedure until the desired colour is achieved.</li> <li><b>MAINTENANCE</b> Regularly clean using Feast Watson FLOORCLEAN. Monitor the surface for signs of colour loss or surface defects. When floor requires an additional coat of LIMING WHITE FLOOR FINISH, apply as per the instructions for Previously Coated Timber.</li> <li><b>THINNING</b> In hot temperatures thin with up to 100mls of water per litre to ease application and slow drying.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	22935	<b>Using Safety Precautions</b>	Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying.
<b>Health Effects</b>	FIRST AID: For advice contact a Doctor or Poisons Information Centre on AUST 13 11 26, NZ 0800 764 766.  SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.  EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.  SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.	<b>Flammability</b>	Non Flammable
<b>Storage</b>	Keep out of reach of children.	<b>Disposal</b>	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage	
<b>Pack A</b>	710W0053
<b>Size</b>	<b>Weight</b>
4L	4.53kg

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.  
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427