

Feast Watson Floorclear Gloss on New Timber Flooring [Interior]

AU_SW14443

Description

Feast Watson FLOORCLEAR is a clear, oil based, polyurethane finish that produces a tough, abrasion resistant finish that enhances the natural beauty of the timber. FLOORCLEAR can be used on new and existing interior timber and cork floors, parquetry and other interior timber subject to high wear, such as benchtops. FLOORCLEAR has been formulated using a lower odour solvent than traditional oil based floor coatings.

Substrate And Substrate Preparation

Substrate Notes:	<p>New, uncoated timber.</p> <p>Comments: Tannin Rich Timber Tannins are water-soluble extractives present in some timbers such as meranti, merbau, kwila, western red cedar and tallowwood. These tannins are leached out by water or moisture and can cause staining of surrounding areas. They are seen as dark coloured stains either under or within a coating.</p> <p>Naturally oily timber Some timbers such as cypress, spotted gum, tallowwood, brush box, teak and yellow balau are naturally oily. These oils can slow down the drying of a coating.</p> <p>Old uncoated timber, which may be grey and weathered, and/or have dry rot, mould, fungus, grain cracking, staining, dirt or other surface contamination. PREVIOUSLY OILED OR STAINED EXTERIOR TIMBER Exterior timber that had been previously coated with either a penetrating oil or stain.</p> <p>Not to be used on previously painted timber. Timber that has been previously coated with either a penetrating oil or stain, or with a film forming coating such as a clear varnish or paint.</p>
Substrate Preparation Notes:	<p>Punch all nail heads approx. 3 mm below surface of timber.</p> <p>Fill nail holes, cracks and other defects with a wood filler and allow to dry thoroughly.</p> <p>Do not use linseed oil putty.</p> <p>Sand in the direction of the grain and along the full length of the boards. Depending on the roughness of the timber, progress through the grades of sandpaper, finishing with a final sand using no finer than 240 grit. Remove all sanding dust.</p>

Coating System Summary

1st Coat:	AUDW0736: Feast Watson Floorclear Gloss
2nd Coat:	AUDW0736: Feast Watson Floorclear Gloss
Optional:	AUDW0736: Feast Watson Floorclear Gloss
Please refer to the coating system details below	

Coating System			
Coat Type:	1st Coat	Datasheet:	AUDW0736 Feast Watson Floorclear Gloss
Application Methods:	   Brush Roller Pad		
	Min	Max	Recommended
Theoretical Spread Rate *		14	14
Wet Film Per Coat (microns)			72
Dry Film Per Coat (microns)			31
Recoat Time **	12 hours		
Coating Application Details:	<p>Stir contents thoroughly before and during application, with a broad flat stirrer. Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil. FLOORCLEAR should be mixed thoroughly, with a flat blade stirrer, before and during application, taking care NOT to introduce bubbles. Apply with a Feast Watson FLOOR FINISH APPLICATOR, brush or short nap mohair roller. Work along the whole length of 3 to 4 floorboards at a time, maintaining a wet edge to prevent lap marks and lay off in the direction of the grain. Take care to not introduce bubbles. When the first coat is thoroughly dry, lightly sand and vacuum to remove dust. Apply second coat as outlined above. A third coat may be required on porous timber or cork to achieve desired gloss level.</p> <p>STAINING Stain bare timber after sanding using Feast Watson PROOFTINT or Feast Watson LIMING SOLUTION as per the application instructions. Seal porous timber such as pine with one coat of Feast Watson TIMBER PRIMER prior to staining to ensure the stain absorbs evenly. To stain flooring, mix PROOFTINT with Feast Watson PROOFTINT COLOUR REDUCER to allow time to evenly work the stain across the floor. Test the colour mix on off-cuts of flooring to confirm the colour before staining the whole area. Apply stain to the floor with a FLOOR FINISH APPLICATOR as per PROOFTINT instructions. Allow 12 hours to dry before applying FLOORCLEAR.</p> <p>MAINTENANCE Allow FLOORCLEAR to cure for a minimum of 4 weeks before polishing. Regularly clean using FLOORCLEAN. Rejuvenate floors with Feast Watson FLOORSHINE POLISH. When floor requires an additional coat of FLOORCLEAR, apply as per the instructions for Previously Coated Surfaces.</p>		
Coat Type:	2nd Coat	Datasheet:	AUDW0736 Feast Watson Floorclear Gloss
Application Methods:	   Brush Roller Pad		
	Min	Max	Recommended
Theoretical Spread Rate *		14	14
Wet Film Per Coat (microns)			72
Dry Film Per Coat (microns)			31
Recoat Time **	12 hours		
Coating Application Details:	<p>Stir contents thoroughly before and during application, with a broad flat stirrer. Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil. FLOORCLEAR should be mixed thoroughly, with a flat blade stirrer, before and during application, taking care NOT to introduce bubbles. Apply with a Feast Watson FLOOR FINISH APPLICATOR, brush or short nap mohair roller. Work along the whole length of 3 to 4 floorboards at a time, maintaining a wet edge to prevent lap marks and lay off in the direction of the grain. Take care to not introduce bubbles. When the first coat is thoroughly dry, lightly sand and vacuum to remove dust. Apply second coat as outlined above. A third coat may be required on porous timber or cork to achieve desired gloss level.</p> <p>STAINING Stain bare timber after sanding using Feast Watson PROOFTINT or Feast Watson LIMING SOLUTION as per the application instructions. Seal porous timber such as pine with one coat of Feast Watson TIMBER PRIMER prior to staining to ensure the stain absorbs evenly. To stain flooring, mix PROOFTINT with Feast Watson PROOFTINT COLOUR REDUCER to allow time to evenly work the stain across the floor. Test the colour mix on off-cuts of flooring to confirm the colour before staining the whole area. Apply stain to the floor with a FLOOR FINISH APPLICATOR as per PROOFTINT instructions. Allow 12 hours to dry before applying FLOORCLEAR.</p> <p>MAINTENANCE Allow FLOORCLEAR to cure for a minimum of 4 weeks before polishing. Regularly clean using FLOORCLEAN. Rejuvenate floors with Feast Watson FLOORSHINE POLISH. When floor requires an additional coat of FLOORCLEAR, apply as per the instructions for Previously Coated Surfaces.</p>		

Coat Type:	Optional	Datasheet:	AUDW0736 Feast Watson Floorclear Gloss
Application Methods:	   Brush Roller Pad		
	Min	Max	Recommended
Theoretical Spread Rate *		14	14
Wet Film Per Coat (microns)			72
Dry Film Per Coat (microns)			31
Recoat Time **	12 hours		
Coating Application Details:	<p>Stir contents thoroughly before and during application, with a broad flat stirrer.</p> <p>Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil.</p> <p>FLOORCLEAR should be mixed thoroughly, with a flat blade stirrer, before and during application, taking care NOT to introduce bubbles.</p> <p>Apply with a Feast Watson FLOOR FINISH APPLICATOR, brush or short nap mohair roller.</p> <p>Work along the whole length of 3 to 4 floorboards at a time, maintaining a wet edge to prevent lap marks and lay off in the direction of the grain.</p> <p>Take care to not introduce bubbles.</p> <p>When the first coat is thoroughly dry, lightly sand and vacuum to remove dust.</p> <p>Apply second coat as outlined above. A third coat may be required on porous timber or cork to achieve desired gloss level.</p> <p>STAINING</p> <p>Stain bare timber after sanding using Feast Watson PROOFTINT or Feast Watson LIMING SOLUTION as per the application instructions.</p> <p>Seal porous timber such as pine with one coat of Feast Watson TIMBER PRIMER prior to staining to ensure the stain absorbs evenly.</p> <p>To stain flooring, mix PROOFTINT with Feast Watson PROOFTINT COLOUR REDUCER to allow time to evenly work the stain across the floor. Test the colour mix on off-cuts of flooring to confirm the colour before staining the whole area.</p> <p>Apply stain to the floor with a FLOOR FINISH APPLICATOR as per PROOFTINT instructions.</p> <p>Allow 12 hours to dry before applying FLOORCLEAR.</p> <p>MAINTENANCE</p> <p>Allow FLOORCLEAR to cure for a minimum of 4 weeks before polishing.</p> <p>Regularly clean using FLOORCLEAN.</p> <p>Rejuvenate floors with Feast Watson FLOORSHINE POLISH.</p> <p>When floor requires an additional coat of FLOORCLEAR, apply as per the instructions for Previously Coated Surfaces.</p>		
Coating System Notes:	<p>* Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application and surface roughness.</p> <p>** Recoat times are quotes for 25°C and 50% relative humidity, these may vary under different conditions.</p>		

Comments
<ul style="list-style-type: none"> Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point. Do not apply if the surface temperature is greater than 40°C or below 10°C, or likely to fall below 10°C during the application or drying period.

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427