

Intergrain Enviropo Timberseal Alcohol Based

AU_DW02517

Part A	701W0310
--------	----------

Description

Intergrain Enviropo Timberseal Alcohol Based is a high performance alcohol based sealer that is suitable for most timber types. Timberseal Alcohol Based enhances the natural colour of interior timber and parquet floors, while helping to reduce the risk of tannin bleed. Timberseal Alcohol Based is lower in odour when compared to traditional solvent based sealers, and is made of 80% sustainably sourced materials. Timberseal Alcohol Based is designed to minimise grain raise. We recommend sanding the 1st topcoat, as not sanding the sealer.

Features

- Enhances natural colour of timber.
- Fast drying - recoat in 1 hour.
- Easy to use.

Uses

Interior timber and parquet floors.



Precautions And Limitations

Do not apply in temperatures above 35°C or below 10°C.
Do not sand sealer.

Performance Guide

Weather	Interior use only.
---------	--------------------

Typical Properties

Number Of Coats	1	V.O.C. Level	<705g/L																								
Touch Dry	30 minutes																										
Clean Up	Other: Methylated Spirits																										
Clean Up Description	Clean all application equipment with methylated spirits. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place used cloths on top of each other.																										
Application Method	 Brush  Roller																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>11.2</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Recoat Time (min)</td><td>1 hour</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td></td><td>10</td></tr> </table>			Solids By Volume	11.2				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	1 hour			Theoretical Spread Rate (m ² /L)			10
Solids By Volume	11.2																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	1 hour																										
Theoretical Spread Rate (m ² /L)			10																								
Typical Properties Notes	Dry times are based on drying conditions of 25°C and 50% relative humidity. DRYING TIMES WILL BE LONGER IN CONDITIONS COOLER THAN 25°C OR MORE HUMID THAN 50% HUMIDITY. Touch Dry: 30 minutes. Recoat: 1 hour.																										

Application Guide

Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants increases the possibility of rejection and delamination. Clean oily timbers such as Brushbox, Spotted Gum, Cypress and Tallowwood with methylated spirits and allow to dry. All previous coatings must be removed back to bare timber by sanding. If uneven, the surface should be sanded with coarse sandpaper. Fine sand the floor finishing with 100 grit sandpaper, then with 150 mesh screen, and vacuum thoroughly with a commercial grade vacuum cleaner to remove any sanding dust.
Application Procedure And Equipment	<ul style="list-style-type: none"> Shake Timberseal Alcohol Based for at least 1 minute prior to use to ensure uniform consistency. <p>It is recommended to shield doorways, fireplaces and windows from dust, dirt or other contaminants settling on the surface between coats, as this will affect the finished appearance. Do not completely seal, as adequate ventilation is required to assist with drying.</p> <p>If using more than one pack of Timberseal Alcohol Based, it is recommended to mix all packs together to achieve product uniformity before use.</p> <p>Apply 1 coat of Timberseal Alcohol Based. Cut in edges using a brush, then apply to the rest of the surface using a 10mm nap microfibre roller.</p> <p>Maintain a wet edge. Do not overwork the coating. Finishing strokes should be in the direction of the timber grain.</p> <p>DO NOT SAND. If sanding is required, apply the first coat of Endure 1 Pack or Endure 2 Pack, allow to dry, then screen with a worn 150 grit or 180 grit screen.</p>

Health And Safety

MSDS Number	DLXGHSEN003121	Using Safety Precautions	Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands, face and all exposed skin thoroughly after handling. Wear protective clothing, gloves, eye/face protection and suitable respirator.
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Seek medical advice.</p> <p>SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.</p>	Flammability	This product is highly flammable.
Fire Suppression	If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).	Protective Equipment	Wear protective clothing, gloves, eye/face protection and suitable respirator.
Storage	Keep out of reach of children. Keep away from heat/sparks/open flames/ hot surfaces. Keep container tightly closed.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	701W0310	Shipment Name	PAINT RELATED MATERIAL
Size 5L	Weight 4.5kg		
Flash Point	<23C	UN Number	1263
Dangerous Goods Class	3	Package Group	I

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427